

## Axicon 6015 Point-of-sale Barcode Verifier

The Axicon 6015 is designed to verify linear barcodes (with a maximum width, including quiet zones, of 66 mm) such as EAN and UPC barcodes used on products scanned at the retail point-of-sale. This verifier is perfect for product manufacturers, label printers, printers and packagers, and pre-press studios. It is widely used by major retailers worldwide.

### Key Features

*User configurable*

*Detailed Reports*

*Automatic variable aperture*

*ISO/IEC compliant verification*

*Lightweight and portable*



The 6015 barcode verifier is designed for use in point-of-sale operations. Lightweight and portable, it requires only a USB connection. The 6015 verifies to ISO/IEC standards, with ANSI reporting as an option. Results are immediately displayed on the screen, and reports can be printed or emailed for remote diagnosis.

Reports may be saved automatically to support ISO 9001 quality control procedures. It features simple user-friendly calibration and configuration of how results are displayed.

The 6015 is perfect for product manufacturers, label printers, printers, packagers, and pre-press studios.

## TECHNICAL SPECIFICATIONS

Dimensions (H x W x D):  
175 x 55 x 75mm

Weight:  
250g (8.82oz)

Construction: ABS plastic, CCD sensor, LED illumination

### PERFORMANCE CHARACTERISTICS:

IP Options: IP50 (60529 rated protection)

Maximum scan width: 66mm (2.6in)

Aperture reference Numbers: 03, 05, 06, 10, and 20

Wavelength of light: 660nm

Calibration logging: Record of date and time for ISO 9001 records

Scanning Technology: EAN-8, EAN-13 and UPC-A (with or without add-ons), UPC-E, GS1 DataBar (all symbols), ITF-14, GS1-128, Code 39, Code 93, Code 128, Codabar, ITF, MSI Plessey (all symbols no wider than 66mm) Laetus pharmacode.

Analysis: All ISO/IEC parameters, ANSI option, decodability per symbol character, nominal x dimension, average bar gain, check digit validation, print contrast measurement (PCS), wide-to-narrow ratio, symbol structure, quiet zones.

Configurable Options: Simplified pass/fail display, number of scans per verification, pass grade, print and file save options, audible warnings, calibration reminder, check digit validation, report generation tool, GTIN validation (with appropriate database), CSV file saving, user data, data checking for various applications

### USER ENVIRONMENTS:

Operating Temperature: 10°C to 40°C (50°F to 104°F)

Relative Humidity: 25% to 80% @ 40°C non-condensing

Storage Temperature: -20°C to 70°C (-4°F to 158°F)

### OPTIONS:

Reflex can configure and supply printers, rewinders and applicators to create an automated workflow.

Reflex Systems also offer a full range of consumables products for your printer: labels, ribbons, print heads and spare parts.

### WARRANTY - TBC:

One year parts and labour – return to bench. \*exclusions apply

### SERVICE COVER:

Reflex operate our own team of field service engineers (all OEM trained) offering 8 hour on-site response (office hours), parts and labour or labour only, to ensure you have cover for your critical activities.

#### For more information

[www.reflex-systems.co.uk](http://www.reflex-systems.co.uk)

#### Reflex Systems Plus

Unit 20 Momentum Place  
Bamber Bridge,  
Preston,  
PR5 6EF

#### Contact

[sales@reflexsystemsplus.co.uk](mailto:sales@reflexsystemsplus.co.uk)

01772 621123

Reflex  
Systems